

# Potstream® Adjustable Flow Patented



The Potstream® is a side mounted watering solution for potted plants and containers. The adjustable gentle stream pattern minimizes soil erosion and the variable flow rate and pattern radius allows for use in various pot sizes.

## Features

- Variable flow rate and pattern size suits pot diameter of 8" and upwards.
- Suits pot wall thickness up to 1.6".
- Side mounted installation for the clean and tidy location of the supply tube.
- Shut-off capability allows easy removal and replacement for relocating of pots and containers.
- Low application rate and gentle stream pattern.
- Easily adjustable knob for varying spray patterns.
- US Design patent D815,929.

## Applications

*Potted plants, planter boxes and containers.*

## Performance Chart

Pressure (psi)	Flow (gph)	Radius (in)
5	0 - 3.3	0 - 8.7
10	0 - 4.7	0 - 9.1
15	0 - 5.8	0 - 9.3
20	0 - 6.8	0 - 9.5
25	0 - 7.7	0 - 10.4
30	0 - 8.3	0 - 11.0
35	0 - 9.1	0 - 11.8
40	0 - 9.7	0 - 12.4

## Ordering Information - Potstream®

Description	Part Number	Pack Quantity	Packs Per Carton	Carton (lbs)
Potstream® Adjustable Flow	31455	25	20	13.9


## Specifications

Dimensions Assembled	UV Stabilized Material	Color	Base/Connection Type
HEIGHT 8.7"	STAKE polypropylene	STAKE black	Inlet: BARB 0.16"
WIDTH 0.9"	KNOB HDPE	KNOB black	
DEPTH 3.0"			
WEIGHT (approx) 0.4 oz			

## Typical System

### KEY

- |                        |                      |
|------------------------|----------------------|
| A - Pressure Regulator | G - Potstream®       |
| B - Nut & Tail         | H - Tee              |
| C - Filter             | I - End Plug         |
| D - Elbow              | J - 1/2" Supply Tube |
| E - Takeoff/Joiner     | K - 1/4" Micro Tube  |
| F - Tidy Bow Elbow     |                      |



**Potstream®**

