
\_ 12" 304.8mm



**DIAL**—Rotate the dial to customize your watering schedule.

+/- Buttons—Use these buttons to adjust time and program. While in AUTO press + to activate Rain Delay.

**ARROW**—Moves cursor around the screen during programming.

**STATION**—Moves between Station 1 and Station 2.

\_MANUAL/CLEAR—Press to water manually or\_ to clear programming.

**RESET**—Press to reset back to factory settings.



**AUTO**—Timer waters according to your customized schedule.

SET CLOCK—Set the time of day.

**START TIME**—Select what time you would like to start watering.

HOW LONG—Determine how long to water HOW OFTEN—Choose how often you will water OFF—Turn off all watering.

#### **Installing the Batteries**

- Remove the tray on the back of the timer by sliding or pulling it out.
- Insert two AA (1.5V) alkaline batteries (not included) and replace the tray.

Note: Firmly replace the battery tray to ensure water resistance and increase battery life. You will know the battery tray is fully inserted if it does not pull out easily. Used up or dead batteries must be removed from the timer and disposed of properly. Replace batteries when low battery icon appears on display. Do not dispose of batteries in fire. Batteries may explode or leak.

## **Programming the Timer** Set Clock and Day



- 1. Turn dial to SET CLOCK.
- Using the +/- buttons, set the time of day, including AM and PM. Timer advances faster if button is held down.
- 3. Press the ARROW button to set current day. 4. Press the +/- buttons to move between and
- Press the +/- buttons to move between and select the current day of the week. Press the ARROW button to toggle back to the time of day.
- 5. Turn dial to save changes

#### Start Time

A start time is the time of day that the timer will begin to water. This timer features three start times.



- 1. Turn dial to START TIME.
- 2. Press the ARROW button to move through and select a start time; A, B, and/or C.

- 3. Press the STATION button to move through and select a station; 1 or 2.
- 4. Using the +/- buttons, set your first start time, including AM and PM. Timer advances faster if button is held down. A box is placed around each programmed start time.

Note: To remove a start time press CLEAR.

5. Repeat steps 2 - 4 to program additional start times.

Note: Only one start time is required.

6. Turn dial to save changes.

#### **How Long**



- 1. Turn dial to HOW LONG.
- 2. Press the STATION button to move through and select a station; 1 or 2.
- Using the +/- buttons, select watering duration from 1 to 360 minutes for each desired station. Timer advances faster if button is held down.

-Note:-To remove-a-watering duration - - - - - press CLEAR.

4. Turn dial to save changes.



Raw Part Num: 24695-24 rA Size (in.): 12" W x 6" H

Size (mm): 304.8 W x 152.4 H

Material: Bleached paper Basis Weight: 18 lbs Caliper: 3.6 Mil

Package Format: Instruction Sheet

100% Scale Outside-face

Outside Color: White Date: 1/29/2014
Designer: J. Smolarski

# 304.8mm

**How Often** SMTWTFSINT (Orbit) 1. Turn dial to HOW OFTEN. 2. Press the ARROW button to move through and select a start time A, B, and/or C. 3. Press + or – button to move the cursor down to select Days of the Week or Interval watering frequency. 4. There are two ways to set your watering frequency for each start time; Days of the \_Week\_or Interval. \_ \_ \_ \_ \_ \_ \_

want to water:

desired day.

of the week on/off.

hours, or 1 to 7 days.

6. Turn dial to save changes.

and stations.

Days of the week - Select specific days you

• Using the ARROW button move to the

Select any combination of days.

• Press the + / - buttons to toggle the day

Interval - Select an interval period you want

• Press the + / - buttons to cycle through each

interval. You may choose to interval water

every 1 hour, 2 hours, 4 hours, 6 hours, 12

5. Repeat steps 2 and 4 to program watering

frequency for additional start times

• Using the ARROW button move to INT.

### Congratulations!

Your timer is now programmed. Turn your dial to AUTO to allow your timer to water according to programmed time, station, duration, and frequency.

#### **Additional Features** Rain Delay



Rain delay allows you to postpone watering for a set period of time. To access the rain delay, follow the steps below

- 1. With the dial on AUTO, press the + button to
- 2. Screen will flash between clock and hours remaining before programmed cycle resumes.
- 3. To remove rain delay, turn dial to OFF and then back to AUTO.

#### Manual/Hand Watering



- select a delay of 1 to 7 days.



#### This feature allows you to water without interrupting your set schedule. To access this

feature, follow the steps below. 1. There are two ways to water: all stations as programmed or selected stations.

#### To water all stations as programmed:

- With the dial on AUTO, press the
- MANUAL button.
- ALL will be displayed and the timer will water all stations as programmed.

### To water specific stations or durations:

- With the dial on AUTO, press the MANUAL button.
- Press the ARROW button to move past the "ALL" selection.

Using the +/- buttons, select watering

- Press the STATION button to select desired station.
- duration from 1 to 360 minutes.

Note: There may be a slight delay between the time the manual button is pressed and when watering begins.

- 2. Screen will flash between clock and time remaining before automatic programming resumes.
- 3. To stop manual watering, turn the dial
- 4. Turn the dial back to AUTO to resume your programmed watering schedule.

#### **Troubleshooting**

Water does not come on at desired time. Check if:

- Clock is set to correct time. including AM and PM.
- Dial is set to "Auto"
- · Start time is set to desired time, including AM and PM.
- Rain Delay is on.

## Timer does not water.

#### Check if:

- Timer is set to AUTO.
- Hose faucet is on.
- Batteries are low.
- Clock is set to correct time, including AM and PM.
- Rain Delay is on.

#### Water won't turn off.

#### Check if:

- HOW LONG is set to desired time.
- HOW OFTEN is set to desired interval hour or day.

#### Working water pressure:

- Minimum: 10 psi
- Maximum: 100 psi

#### Working temperature:

- Maximum: Do not exceed 120°F
- Minimum: Keep from freezing

#### -Warnings: - -

For outdoor use with cold water only. Not for use with appliances.





1-800-488-6156

Orbit® Irrigation Products, Inc. North Salt Lake, UT 84054

© 2014 Orbit Irrigation Products, Inc. All rights reserved. All trade names are registered trademarks of respective manufacturers listed.

PN 24713-24 rA

Raw Part Num: 24695-24 rA Size (in.): 12" W x 6" H Size (mm): 304.8 W x 152.4 H

Material: Bleached paper Basis Weight: 18 lbs Caliper: 3.6 Mil

Package Format: Instruction Sheet

100% Scale Outside-face

Outside Color: White Date: 1/29/2014 Designer: J. Smolarski

152.4mm